



|                          |                            |
|--------------------------|----------------------------|
| Including bulb           | Yes                        |
| Luminous Flux (Lumen)    | 4320lm                     |
| Luminous Efficacy (lm/W) | 130                        |
| IP-rating                | IP40                       |
| Impact Protection (IK)   | IK02 - 0.20 joule          |
| Fixture Connection       | Screwless terminal, 5-Pole |
| Finish of Reflector      | Frosted                    |
| Power factor             | >0.90                      |
| Product Type Category    | LED Panel                  |

## Fixture Information

|                       |                                |
|-----------------------|--------------------------------|
| Mounting Method       | Recessed                       |
| Unified Glare Rating  | < 19 - for offices and schools |
| Optical Cover         | PS (Polystyrene)               |
| Operating Temperature | -10 to +50                     |
| Emergency Lighting    | No Emergency Unit              |
| Colour of the Fixture | White                          |
| Housing               | Aluminium                      |
| Colour of material    | White                          |

## Dimensions

|                |             |
|----------------|-------------|
| LED panel size | 62.5x62.5cm |
| Length (mm)    | 620         |
| Width (mm)     | 620         |
| Height (mm)    | 32          |

## Sensor Information

Type of sensor

No Sensor

### Why Any-lamp?



Order from the **largest lighting specialist** in Europe



**Customised** quotation



Up to **7 years warranty**



**Easy** return process

