



Specifications Philips LED Panel  
CoreLine RC132V 31W 4300lm -  
830-835-840 CCT | 60x60cm - UGR <19  
- Interact Dimmable

[View Product](#)

General Information

|                          |                                      |
|--------------------------|--------------------------------------|
| SKU                      | 249718                               |
| EAN                      | 8720169751316                        |
| Manufacturer Code        | 8720169751316                        |
| Brand                    | Philips                              |
| Manufacturer Name        | RC132V G6 40_43S/830_40 WIA 60x60 OC |
| Any Lamp all-in warranty | 5 Years                              |
| Average Lifetime (h)     | 100000                               |
| Series                   | CoreLine                             |

Technical Information

|                             |                                                   |
|-----------------------------|---------------------------------------------------|
| Technology                  | LED Integrated                                    |
| Replaces (Watt)             | 4x18                                              |
| Wattage                     | 31W                                               |
| Voltage (V)                 | 220-240                                           |
| Dimmable                    | Dimmable with Philips Interact                    |
| Colour Code                 | 835 Warm White, 830 Warm White, 840 Cool White    |
| Colour temperature (Kelvin) | 3500 Warm White, 3000 Warm White, 4000 Cool White |
| Colour Rendering (Ra)       | 80-89                                             |
| Colour of Light             | White                                             |
| Light colour options        | CCT                                               |

|                          |                    |
|--------------------------|--------------------|
| Luminous Flux (Lumen)    | 4300lm             |
| Luminous Efficacy (lm/W) | 140                |
| IP-rating                | IP20               |
| Impact Protection (IK)   | IK02 - 0.20 joule  |
| Fixture Connection       | Screwless terminal |
| Power factor             | >0.90              |
| Product Type Category    | LED Panel          |

## Fixture Information

|                       |                                |
|-----------------------|--------------------------------|
| Mounting Method       | Recessed                       |
| Unified Glare Rating  | < 19 - for offices and schools |
| Optical Cover         | Opal                           |
| Colour of the Fixture | White                          |
| Housing               | Steel                          |
| Colour of material    | White                          |

## Dimensions

|                |         |
|----------------|---------|
| LED panel size | 60x60cm |
| Length (mm)    | 595     |
| Width (mm)     | 595     |
| Height (mm)    | 70      |

## Sensor Information

## Why Any-lamp?

|                                                                                                                                                                                                                                                                   |           |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------|
| Type of sensor                                                                                                                                                                                                                                                    | No Sensor |
|  Order from the <b>largest lighting specialist</b> in Europe  <b>Customised</b> quotation |           |
|  Up to <b>7 years warranty</b>  <b>Easy</b> return process                                  |           |